

BREMEN 20001

Advanced Comfort Safety Shoe



Sex	Sizes	Colour	Accreditations
Male	5-13	Black	SANS / ISO 20345



RECOMMENDED ENVIRONMENT:

This shoe has been engineered to provide the wearer with protection in an array of harsh conditions. This shoe includes technological advancements in comfort and carries the approval of the Podiatry Association of South Africa. This shoe has found popularity amongst workers who are on their feet for long periods of time

UPPER:

- Cut from 2.0mm - 2.2mm Full Grain Printed Water Buffalo sides with Nubuck Leather trimmings
- Increased girth area as per podiatry specifications
- Padded bellows tongue is from a closed cell foam and made from a combination of Nubuck and Buffalo Leather
- The padded collar is from a closed cell foam
- 3 pair D-Ring lace-up and hooks with corrosion-resistant gunmetal coating
- Braided lace from polyester yarn and central core for additional strength

LINING:

- The quarter lining is from an industrial ferrabelle non-woven material
- The vamp lining is from a hi-tech needle-fibre blend with excellent perspiration absorbency and treated with *Ultra-Fresh to impart hygienic and anti-bacterial properties to the material

IN-SOCK & TOP SOCK:

- The in-sock is from an anti-static non-woven material that is bonded to a layer of EVA and contains Poron inserts at the heel and ball of the foot for enhanced comfort and support
- The Energiser Poron / EVA top sock is from a combination of polyester and wool, with excellent perspiration absorbency, and bonded to a layer of EVA
- The Poron inserts at the ball and heel of the top sock offer optimum support where it is needed most, ensuring dynamic impact compression and a gentle rebound with every step
- The top sock responds to weight and temperature, molding itself to the foot, resulting in fewer aches and pains
- The top sock has been treated with *Ultra-Fresh to impart hygienic and anti-bacterial properties to the material

SOLE:

- The sole is from Double Density PU/PU
- The midsole is from a low density flexible Polyurethane with a shore hardness of 0.45mm - 0.5mm
- The outer sole is from Polyurethane with a shore hardness of 0.64mm - 0.65mm
- The shoe is engineered with an EVA insert at the heel for shock absorption
- A shank reinforcement is molded into the midsole for additional arch support
- The shoe can withstand temperatures up to 95°C
- The shoe is anti-static
- If required, this shoe can be manufactured with a steel midsole - 20701

TOE CAP:

- Steel toe cap - extra-wide fitting
- Can withstand an impact load of 200 joules

The Bremen shoe has been tested to comply with SANS/ISO 20345 specifications and carries the SANS/ISO 20345 certified mark.

This product is manufactured at Beier Safety Footwear, a division of BBF Safety Group (Pty) Ltd, which is an ISO 9001:2000 accredited factory.

[NRCS/9002/287766/0162](#)

JULY 2018

*Ultra-Fresh is a registered trademark of Thomson Research Associates, Inc.