



PRODUCT CODE: HP-HALOVISOR

PRODUCT DESCRIPTION: HALO Helmet Visor

PRODUCT COMPLIANCE

EN/ISO REQUIREMENT	Certified to EN ISO 16321-1:2022.
IMPACT LEVEL	C.
MARKINGS	CE 16321 RSG C 1-M.
OPTICAL CLASS	1.
PACKAGING	1 per box; 40 per carton.
SIZING	Head size: 1-M.

MATERIALS AND FEATURES

- **Lens Material:** clear Polycarbonate.
- Compatible with REBEL Halo range helmets.
- Scratch-resistant coating.
- Anti-fog coating on both sides.
- Slides up for storage, when not in a working position.
- Clear, detachable helmet visor.

STORAGE AND CLEANING

- Visors should be stored at temperatures between 5°C and 40°C, with relative humidity not exceeding 90%.
- Keep away from solvents, solvent vapours and any corrosive materials, as these, may significantly reduce the impact protection of the visor.
- The maximum product life of the visor is 3 years from date of manufacture; however various factors may result in a shorter lifespan.
- Can be cleaned with soap and water and may be disinfected with any common household disinfectant.

WARNINGS

- Any visors that have been subjected to impact must not be used and should be discarded and replaced.
- This visor does not provide protection against IR radiation and must not be used as primary protection in environments where hazardous levels of IR radiation is present, such as during welding operations or the casting of molten metal.

SUGGESTED ENVIRONMENTS

- General work e.g. Construction, mining, forestry and agriculture.
- Working at Heights.