

Cate / 54002

## Dual Density Polyurethane Sole

Manufactured with direct injection-moulded dual density polyurethane for more comfort and protection in heavy industrial environments.

| Sex    | Sizes | Colour | Accreditations |
|--------|-------|--------|----------------|
| Female | 2 - 9 | Black  | EN/ISO 20345   |



SRC  
SLIP  
RESISTANCE  
RATING

EN



## Standard Fit

### Upper:

- Cut from 2.0 - 2.2mm smooth Full Grain Leather
- 20mm padded collar from synthetic material for enhanced comfort and support
- 10mm padded tongue from synthetic material for improved comfort
- 3 pair rust resistant D-ring lace-up with 1 pair hooks for quick removal of boot
- Braided lace from polyester yarn and central core for additional strength

### Lining:

- The quarter lining is from an industrial ferrabelle non-woven material
- The vamp lining is from a hi-tech needle-fibre blend with excellent perspiration absorbency and is treated with **Ultra-Fresh\*** to impart hygienic and anti-bacterial properties to the material

### In-Sock & Top Sock:

- The in-sock is from an anti-static non-woven material
- The Energiser top sock is from a combination of polyester and wool, with excellent perspiration absorbency
- The top sock features EVA foam inserts on the ball and heel area for enhanced comfort and shock absorption
- The top sock has been treated with **Ultra-Fresh\*** to impart hygienic and anti-bacterial properties to the material

### Sole:

- The sole is from a dual density PU/PU
- The midsole is from a low density flexible Polyurethane with a shore hardness of 0.45mm - 0.50mm
- The outer sole is from Polyurethane with a shore hardness of 0.64mm - 0.65mm
- A shank reinforcement is moulded into the midsole for additional arch support
- This boot can withstand temperatures of up to 95°C
- This boot has a SRC slip-resistance rating
- This boot is anti-static

### Toe Cap:

- Steel toe cap
- Can withstand an impact load of 200 joules

The Cate boot has been tested to comply with EN/ISO 20345 specifications and carries the EN/ISO 20345 certified mark

This product is manufactured in South Africa by BBF Safety Group (Pty) Ltd. in an ISO 9001:2000 accredited factory.

**FEBRUARY 2020**